

WEST Generate Collection

L12: Entry 1 of 5

File: DWPI

Aug 4, 1999

DERWENT-ACC-NO: 1999-446259

DERWENT-WEEK: 200029

COPYRIGHT 2001 DERWENT INFORMATION LTD

TITLE: A simple method of manufacturing a fuel cell separator that does not produce bubbles

INVENTOR: MIZUNO, S

PRIORITY

PRIORITY-DATA: 1998JP-0022752 (January 19, 1998)

PATENT-FAMILY:

| PUB-NO | PUB-DATE | LANGUAGE | PAGES | MAIN-IPC |
|---------------|----------------|----------|-------|------------|
| EP 933825 A2 | August 4, 1999 | E | 013 | H01M008/02 |
| JP 11204120 A | July 30, 1999 | | 011 | |
| CA 2259748 A1 | July 19, 1999 | E | 000 | B29C043/02 |

INT-CL (IPC): B29B 9/08; B29C 43/02; H01M 2/14; H01M 8/02

ABSTRACTED-PUB-NO: EP 933825A

BASIC-ABSTRACT:

NOVELTY - A fuel cell separator containing epoxy and phenolic binders, which do not generate gas bubbles, and hence maintains the gas impermeability of the separator, is made by:

- A) preparing a raw material by mixing carbon, an epoxy resin and a phenolic resin;
- B) charging the raw material into a mold;
- C) heat press forming the raw material in the mold.

USE - The separator is used in fuel cells.ADVANTAGE - The separator is prepared using a simple manufacturing process, but does not produce any gas bubbles that reduce the gas permeability.

ABSTRACTED-PUB-NO: EP 933825A

EQUIVALENT-ABSTRACTS:

CHOSEN-DRAWING: Dwg.0/9